

AUTOMATIC DISPENSER

D810 NEO



» BETTER DISPENSING WITH COMPACT DESIGN



The D810 Neo vending machine is a new generation self-service machine that transforms the warehouse into a modern dispensing center. The machine can dispense up to 810 different products. The design is based on the principle of a rotating drum, which makes it possible to store a very large number of articles in a small space. Intuitive and intelligent management is provided by a large 15.6" display. The D810 Neo has a built-in QR code reader, regardless of the version of the device selected. The machine in MASTER version allows the OEM devices to be powered without connecting to a 230V power supply. All you need to do is plug the Master machine into the socket to get the OEM devices working. The D810 NEO is probably the first vending machine in the world with a built-in inventory assistant.

PRODUCT COMPARTMENT ADJUSTMENT FUNCTION

The machine's impressive load capacity is achieved by the function of adjusting the compartments in width and height, in 9 configurations. The shelves can be of different sizes. The easy change of settings allows the capacity of the machine to be adapted to the current needs.

PRODUCT LOADING OPTIONS



DOOR OPENING

Optimal for refilling large quantities of products of the same type.

2

THROUGH FLAPS IN THE DOOR OF THE MACHINE

Recommended for different types of articles.

3

DRUM SCANNING SYSTEM

Detects where products have been loaded. This significantly reduces loading time, making it useful for products in larger quantities as well as individual items.

AUTOMATIC DISPENSER **D810 NEO**



» NEW GENERATION - BETTER DISPENSING WITH COMPACT DESIGN

TECHNICAL SPECIFICATIONS					
Height [mm]			1950		
Width [mm]			795		
Depth [mm]			795		
CAPACITY [COMPARTMENTS/SHELVES OF ONE TYPE]					
50 × 80 mm			810		
75 × 80 mm			540		
50 × 170 mm			405		
150 × 80 mm or 75 × 170 mm or 50 × 270 mm			270		
75 × 270 mm			180		
150 × 170 mm			135		
150 × 270 mm			90		
OTHER					
Operating temperature [°C]			5 - 40		
Weight [kg]			400		
Current consumption [watts]			standby: 15 / distribution: 100		
Voltage [V]			230 / 1 A		
Permissible load for basic drum configuration [kg]				500	
DIMENSIONS IN MM	NUMBER OF COMPARTMENTS	Α	В	С	D
A C	810	80	50	275	10
	540	80	75	275	15
	270	80	150	275	30
	405	170	50	275	10
	270	170	75	275	15
	135	170	150	275	30
	270	270	50	275	10
	180	270	75	275	15

270